

Multi-Mode Jumper Cable / Patch Cord (FC, SC, LC, ST)

Specifications

Contact Hengyan Photonics with your custom specification needs.

Parameter		Unit	PC / APC
Insertion Loss (23°C, All SOP)	Max	dB	0.3
Exchange	Max	dB	0.2
Repeatability	Max	dB	0.2
Durability	Min	Cycles	1000
Optical Power Handling	Max	mW	300
Operating Temperature		°C	-5 to 70
Storage Temperature		°C	-40 to 85

* SOP-State Of Polarization

Ordering Information

Contact Hengyan Photonics with your custom configuration needs.

MMJP	Fiber Type	Connector-1	Connector-2	Cable Type	Fiber Length
MMJP	M5=50/125 Multimode	FC=FC/PC	FC=FC/PC	B= 250um	10=1.0m
	M6=62.5/125 Multimode	FA=FC/APC	FA=FC/APC	L= 900um	15=1.5m
	X=Others	LC=LC/PC	LC=LC/PC	W=2mm	20=2.0m
		LA=LC/APC	LA=LC/APC	H=3mm	30=3.0m
		SC=SC/PC	SC=SC/PC	X=Others	X=Others
		SA=SC/APC	SA=SC/APC		
		ST=ST/PC	ST=ST/PC		
		X=Others	X=Others		