

Single-Mode N-Port Optical Circulator (1310, 1480, 1550, or 1590nm)

Specifications

Contact Hengyan Photonics with your custom specification needs.

Parameter		Unit	Value
Center Wavelength		nm	1310, or 1480, or 1550, or 1590
Operating Wavelength Range		nm	$\lambda_c \pm 20$
Transmitting Direction		-	1→2, 2→3, ... N-1→N
Isolation (23°C, All SOP) (2→1, or 3→2, ... N→N-1)(23°C)	Typ.	dB	55
	Min	dB	40
Insertion Loss (23°C, All SOP) (1→2, or 2→3, ... N-1→N)	Typ.	dB	0.8
	Max	dB	1.0
PDL	Max	dB	0.2
PMD	Max	ps	0.2
Return Loss	Min	dB	55
Directivity (a & b not consecutive: a→b, or b→a)	Min	dB	50
Optical Power Handling	Max	mW	300
Package Dimension	mm		75 x 32 x 10
Operating Temperature	°C		-5 to 70
Storage Temperature	°C		-40 to 85

* The above specifications are for parts without connectors. Adding connectors can affect the IL, RL, & PDL.


* SOP=State Of Polarization

Ordering Information

Contact Hengyan Photonics with your custom configuration needs.

CIR	Port	Wavelength	Fiber Type	Fiber Length	Connector	Package
CIR	3=3-Port	13=1310nm	B= SMF-28, 250um	10=1.0m	NE=None	Box = Standard Box
	4=4-Port	14=1480nm	L= SMF-28, 900um	15=1.5m	FA=FC/APC	
	5=5-Port	15=1550nm		20=2.0m	FC=FC/PC	X=Others
	6=6-Port	159=1590nm		30=3.0m	SA=SC/APC	
	7=7-Port		X=Others		SC=SC/PC	
	8=8-Port	X=Others		X=Others	ST=ST/PC	
					LA=LC/APC	
					LC=LC/PC	
					X=Others	

Package Dimensions



Package shown with 6 ports.