

Multi-Mode Fiber Pigtail (Fiber Tip) (850/1310nm)

Specifications

Contact Hengyan Photonics with your custom specification needs.

Parameter		Unit	Value
Wavelength		nm	850/1310
Reflection (AR-Coating)	Max	%	0.25
Return Loss	Min	dB	8° -
Polish Angle (θ)		Degree	0° -
Fiber Diameter (d)		um	0±0.5, or 8±0.5
Scratch/Dig		-	125
Package Dimension	Diameter (O.D.)	mm	10/5
	Length (L)	mm	1.8±0.02, or 1.0±0.02
Fiber Type		-	5.5±0.5/6.5±0.5
Optical Power Handling		mW	50/125
Operating Temperature		°C	300
Storage Temperature		°C	-5 to + 70
			-40 to +85

* The above specifications are for parts without connectors. Adding connectors can affect the IL, RL, & PDL.

* The connector key is aligned to slow axis.

Ordering Information

Contact Hengyan Photonics with your custom configuration needs.

FP	Type (Orientation)	Wavelength	O.D.	Angle Polish	Fiber Type	Fiber Length	Connector
FP	S=Single Fiber	00=No AR Coating	10=1.0mm	0=0-degree	B=SMF-28, 250um	10=1.0m	NE=None
	DT=Dual Fiber T Type	98=980nm	18=1.8mm	8=8-degree	L= SMF-28, 900um	15=1.5m	FA=FC/APC
	DH=Dual Fiber H Type	10=1060nm				20=2.0m	FC=FC/PC
	TT= Tri-Fiber Triangle	35=1260-1620nm	X=Others	X=Others	X=Others	30=3.0m	SA=SC/APC
	TLT=Tri-Fiber Linear T Type	95=980/1550nm				X=Others	SC=SC/PC
	TLH=Tri-Fiber Linear H Type	X=Others					ST=ST/PC
							LA=LC/APC
							LC=LC/PC
							X=Others

*Only a Single-Fiber configuration can be used with a 1.0mm O.D.

Product Diagram

