

Photodiode: Multi-Mode Fiber-Pigtail (1250-1650nm)

Specifications

Contact Hengyan Photonics with your custom specification needs.

Parameter			Unit	Value
Wavelength			nm	1250-1650 [^]
Dark Current	(V _R =-5V, 25°C)	Max	nA	1.0 [^]
Response Time	(V _R =-5V, R _L =50 Ω)	Typ.	ns	1 [^]
Responsivity	(V _R =0V, λ=1310nm) (V _R =0V, λ=1550nm)	Min	A/W	0.8 [^]
		Min	A/W	0.85 [^]
Active Diameter		-	um	300 [^]
Bandwidth	(R _L =50Ω, Pin=10dBm, V _R =-5V, Small Signal)	Min	GHz	0.4 [^]
Capacitance	(V _R =-5V, f=1MHz)	Max	pF	7 [^]
Reverse Voltage		Max	V	20 [^]
Forward Current		Max	mA	6 [^]
Return Loss (λ=1550nm, 23°C)		Min	dB	30 [*]
Input Optical Power		Max	mW	5 [^]
Storage Temperature			°C	-40 to 85
Operating Temperature			°C	0 to 70

* The above specifications are for parts without connectors. Adding connectors can affect the Responsivity, Return Loss.

[^] The above parameters depend on the photodiode type.

Ordering Information

Contact Hengyan Photonics with your custom configuration needs.

MMPPD	Type	Material	Active Diameter	Package	Dimensions	Fiber Type	Fiber Length	Connector
MMPPD	PIN=PIN	IGA=InGaAs	3.00=300um	T46=TO-46	5523= Φ5.5 x L23	M5B=50/125um, 250um M5L=50/125um, 900um M6B=62.5/125um, 250um M6L=62.5/125um, 900um	10=1.0m 15=1.5m	NE=None FA=FC/APC FC=FC/PC SA=SC/APC SC=SC/PC
	X=Others	X=Others	X=Others	X=Others	X=Others	X=Others	X=Others	X=Others

Package Dimensions

